

DECLARATION OF PERFORMANCE

No. **BETUN 10/20**

1. Name and identity code:

Bitumen for paving CEPSASFALT 10/20 BETUN 10/20 **(E**

2. Name and address of manufacturer:

CEPSA COMERCIAL PETRÓLEO, S.A. Pº de la Castellana, nº 259 A – Torre CEPSA 28046 Madrid (Spain)

Tel.: 91 337 60 00 www.cepsa.es

3. Applications:

Construction and maintenance of roads, airport runways and other paved areas

4. System of assessment and verification of performance compliance: 2+

5. Notified body:

• AENOR 0099

• Task performed: Factory control assessment

• Certificates: 0099/CPR/B11/0199 – Date issued: 30/07/2010 0099/CPR/B11/0208 – Date issued: 30/07/2010

6. Declared performance:

Essential characteristics	Performance	Harmonised technical specifications
Consistency at intermediate service temperatures		
Penetration at 25° C	Class 3	
Consistency at high service temperatures		
Softening point (60°C – 70°C)	Class 4	
Dynamic viscosity at 60°C	Class 0	
Durability of the consistency at intermediate service		
temperatures, with the test method used		EN 13924:2006
Change of mass (EN-12607-1)	Class 2	EN 13924.2000
Retained penetration (EN-1426)	Class 2	
Durability of the consistency at high service temperatures,		
with the test method used		
Softening point after hardening	Class 0	
Increased softening point (EN 14274)	Class 2	
Penetration rate before hardening (Appendix A)	Class 2	



- The performance of the product declared in point 1 is in conformity with the declared performance in point 6.
- This declaration of performance is issued at the sole responsibility of the manufacturer identified in point 2.
- Signed by and on behalf of the manufacturer by:

Gerardo Pardo Alvarez-Buylla Director of the Asphalt Unit CEPSA COMERCIAL PETRÓLEO, S.A.

Madrid, 30 april 2021