



Mobil Vacuoline 500

Industrial Mobil, United States

Circulating Oils

Product Description

The Mobil Vacuoline 500 Series family of products provides a versatile lubricant source for a wide range of industrial equipment. The Mobil Vacuoline 500 Series of lubricants are high performance heavy duty circulating oils designed for the demands of No-Twist Rod mills, however their all round performance makes them a excellent choice for circulation systems lubricating gears and bearings. Mobil Vacuoline 500 Series are designed to meet the critical requirements of the Morgan Construction Company's high speed No-Twist Rod Mills, as well as the circulation oil requirements of Danielli rod mills.

They are formulated from high quality base stocks and a proprietary additive system to provide superior wettability, extra oil retention and thin film protection against rust and corrosion. Mobil Vacuoline 500 gives excellent resistance to oxidation and thermal degradation, and a high level of protection against wear. They possess excellent demulsibility that permits water and other contaminants to separate readily from the oil in the system reservoir. The Mobil Vacuoline 500 Series are available in six viscosity grades.

Features and Benefits

The Mobil Vacuoline 500 Series family of products is well known and highly regarded world-wide based on their outstanding performance and the Research and Development expertise and global technical support which stand behind the brand. The highly versatile performance of Mobil Vacuoline 500 Series oils, has made them the choice of many users around the world for many decades.

Mobil Vacuoline 500 series are designed for lubrication of circulation systems of No-Twist Rod Mills, industrial and marine gearboxes, hydraulic systems plus a wide variety of ancillary equipment.

Features	Advantages and Potential Benefits
Good protection against rust and corrosion through a balanced high performance lubricant formulation	Fewer unscheduled stoppages and lower maintenance costs
Outstanding antiwear performance	Excellent protection of critical bearings and gears
Excellent water separation characteristics	Rapid separation of water for smooth, efficient operation, reduced downtime and undiminished wear protection

Features	Advantages and Potential Benefits
High resistance to oxidation and thermal degradation	Long oil charge life and avoidance of costs of unanticipated production interruptions
Multiple application capability	Inventory Savings

Applications

These oils are intended primarily for the lubrication of plain bearings, roller bearings, parallel shaft and bevel gearing. They are suitable as multipurpose lubricants in systems not subject to shock loading and which do not require extreme pressure performance. The Mobil Vacuoline 500 series possess good demulsibility that is retained under conditions of severe water contamination. Mobil Vacuoline 500 series are used in applications using splash, bath and ring oil arrangements and all other application methods involving pumps, valves and auxiliary equipment. They are recommended for use in hydraulic systems where higher viscosity oils are specified. They are particularly resistant to the effects of prolonged high temperature exposure and perform well in circulating systems with short oil residence times.

Typical applications include

- No Twist Rod Mills
- Moderate duty spur, bevel, helical and herringbone gear units
- Circulating systems
- Mobil Vacuoline 525, 528, 533 can also be used in hydraulic systems employing gear, vane, radial and axial piston pumps where high viscosity anti-wear hydraulic fluids are required.
- Certain compressors and vacuum pumps handling air and inert gases provided the discharge temperatures do not exceed 150oC , not suitable for breathing air compressors

Specifications and Approvals

Mobil Vacuoline 500 Series meets or exceeds the requirements of:	525	528	533	537	546	548
Morgan Construction Company's "No-Twist® Rod Mill Lubricants Specification	X					
Danieli Type 21-0.002117.R BGV No Twist Stand Block-TMB/TFS Rev 14	X					

Typical Properties

Mobil Vacuoline 500 Series	525	528	533	537	546	548
ISO Viscosity Grade	-	150	220	320	460	680
Viscosity, ASTM D 445						
mm ² /s @ 40°C	89	146	215	309	453	677

Mobil Vacuoline 500 Series	525	528	533	537	546	548
mm ² /s @ 100°C	10.7	14.4	18.8	24.4	29.4	36.9
Viscosity Index, ASTM D 2270	99	96	96	96	95	89
Pour Point, °C, ASTM D 97	-24	-21	-15	-12	-12	-9
Flash Point, °C, ASTM D 92	264	272	284	288	286	286
Specific Gravity @ 15.6 °C kg/l, ASTM D 1298	0.88	0.89	0.89	0.89	0.90	0.92
Demulsibility at 54 °C, ASTM D 1401, Minutes to 37ml water	15	-	-	-	-	-
Demulsibility at 82 °C, ASTM D1401 Minutes to 3ml	-	10	15	20	25	5
Demulsibility for non-EP oils, ASTM D2711, ml water	39	38	36	39	35	36
Rust Protection, ASTM D665						
Distilled Water	Pass	Pass	Pass	Pass	Pass	Pass
Sea Water	Pass	Pass	Pass	Pass	Pass	Pass
Foaming Characteristics, ASTM D 892Seq I, II, III; Tendency/Stability, ml/ml						
Seq I	10/0	5/0	5/0	10/0	5/0	0/0
Seq II	0/0	0/0	0/0	0/0	0/0	0/0
Seq III	0/0	0/0	0/0	0/0	0/0	0/0
Copper Corrosion, ASTM D130 3 hours @ 100°C	1A	1A	1A	1A	1A	1A
FZG Gear Test, DIN 51354, Failure Stage	12	12	12	12	12	12

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Toxicity class: free BAG T No.: 611500

The Mobil logotype, the Pegasus design and Vacuoline are trademarks of Esso Mobil Corporation, or one of its subsidiaries.

07-2016

Exxon Mobil Corporation

22777 Springwoods Village Parkway
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

© Copyright 2003-2017 Exxon Mobil Corporation. All Rights Reserved.